



## General Product Information

**Rolling Rock Building Stone, Inc.**  
**40 Rolling Rock Road**  
**Boyertown, PA 19512**  
**Phone: 610.987.6226**  
**RealStoneVeneer.com**



Category	Product	Shape Description (Format)	Typical Thickness Range	Typical Face Size Range	Typical Weight Per Square Foot	General Stone Type	L-Corner (Y or N)	Density (lbs/cuft) ASTM C97	Absorption (%) ASTM C97	Compressive Strength (PSI) ASTM C170	Modulus of Rupture (PSI) ASTM C99
Fieldstone	Huntington Gray®	Irregular	0.50" to 1.5"	4"-15" Dia.	12	Quartzitic Sandstone	Y	158	0.91	22,650	2110
	Brookfield Buff®			4"-15" Dia.	12						
	Chesterbrooke Blend®			4"-12" Dia.				156	0.71	21,500	4040
	Mountain Fieldstone™			4"-14" Dia.	14			167	0.36	26,830	3850
	Chestnut Traditional™	Roughly Square	4"-20" Long 4"-10" High	12		158	0.91	22,650	2110		
	Pine Forge™	Irregular	4"-15" Dia.	12	Gneiss		N/A	N/A	N/A	N/A	
Ledge Rock	Hawk Mountain™	Ledge Rock	0.50" to 1.5"	4"-20" Long 2"-6" High	12	Quartzitic Sandstone	Y	158	0.91	22,650	2110
	Hickory™			4"-20" Long 2"-5" High				158	0.91	22,650	2110
	Mountain Fieldstone™			4"-20" Long 2"-5" High				167	0.36	26,830	3850
	Stonemont®			4"-16" Long 3"-7" High				158	0.91	22,650	2110
Sandstone	Appalachian Blue™	Irregular	0.50" to 1.5"	4"-15" Dia.	14	Sandstone	N	N/A	N/A	N/A	N/A
	Alpine Green™			4"-15" Dia.	14						
	Russet Brown™	Ashlar Blend	4"-20" Long 2"-10" High	12	Y		153	2.6			
Quartzite	Deer Creek™	Irregular	0.50" to 1.5"	4"-15" Dia.	13	Quartzite	N	N/A	N/A	N/A	N/A
	Gold Strike™			4"-20" Dia.							
	Rustic Monarch™										
	Silver Sunrise™										
Limestone	Alverson Limestone®	Irregular	0.50" to 1.5"	4"-15" Dia.	12	Limestone	Y	170	0.34	21,050	3340
		Ashlar Blend		4"-16" Long 3"-10" High							
	Seneca Limestone® buff	Irregular		4"-15" Dia.				165	1.42	14,900	3350
		Ashlar Blend		4"-20" Long 3"-10" High							
	Seneca Limestone® gray	Irregular		4"-15" Dia.				165	1.75	15,100	2780
		Ashlar Blend		4"-20" Long 3"-10" High							
	Crestwood™	Ashlar Blend	0.50" to 1.5"	4"-20" Long 3"-8" High	13		132	5.4	2,964	N/A	
	Piedmont™					155	2.26	13,393	1955		
Granite & Mica	Arcadian™	Ashlar Blend	0.50" to 1.5"	4"-20" Long 3"-10" High	12	Granite Gneiss	Y	175	0.06	14,486	2828
	Algonquin™			13	N/A			0.28	9750	2053	
	Lake Harmony™			13	N/A			0.26	12,220	2648	
	Bryn Mawr™	Irregular		4"-15" Dia.	14		N	N/A	N/A	N/A	N/A
	Hemlock Brown™			4"-15" Dia.	14						
	Crystal Lake®	Ashlar		4"-20" Long 2"-5" High	12	Schist	Y	168	0.38	32,380	4100
	Foxcroft™			4"-20" Long 3"-9" High				N/A	N/A	N/A	N/A
	Wissahickon Schist™	Ashlar Blend		4"-20" Long 2"-10" High				167	0.45	16,700	2590

For additional information, please consult [www.RealStoneVeneer.com](http://www.RealStoneVeneer.com)

Products as listed are sold nationally by Rolling Rock Building Stone, Inc. and its authorized resellers under the brand name RealStone Veneer™. All items marked with the ™ symbol are trademarks and the Rolling Rock Building Stone, Inc. logo is a registered trademark of Rolling Rock Building Stone, Inc.

RealStone Veneer™ is a natural stone product. It is provided to you "AS IS" without warranty of any kind, either express or implied, including, but not limited to the implied warranties of merchantability or fitness for a particular purpose.

Natural Stone is a relatively hard, naturally formed mineral or petrified matter, produced in nature. Therefore, considerable variations including, but not limited to, color, texture, size, and cleft will occur in all natural stone. Samples, sample panels, brochures, photographs, computer-generated pictures, and items viewed on the Internet may be, in some measure, different from the stone you actually receive. Laboratory tests, if conducted, are performed on small samples and cannot be totally accurate because of the limited scale of the tests. Please be sure that all parties involved are aware of these facts, so an informed decision can be made regarding natural stone.

The recommended installation procedure for RealStone Veneer™ is Laticrete® MVIS as it is defined on their website [www.laticrete.com/mvis](http://www.laticrete.com/mvis) and is published in their literature. Laticrete® also offers a limited warranty that applies to both the system and the installed stone product. This limited warranty applies only when Laticrete® specifications and products are implemented. Contact Laticrete® directly by using their website for more information. Rolling Rock Building Stone, Inc. does not manufacture this system, but has endorsed Laticrete® MVIS as the recommended installation system for all of its adhered veneer brands.

When possible, choose an installing contractor that fits your desired application, rather than one that fits your budget. For a detailed explanation, contact your local RealStone Veneer™ representative.

User accepts all responsibility if a 'dry stack' application is performed on any exterior project.

Use of Chemicals: Acid or chemical cleaners are not recommended because of the inability of the user to control its use. User accepts all risks.