

Rolling Rock Building Stone Inc. 40 Rolling Rock Rd Boyertown, PA 19512 Phone: 610-987-6226, Fax 610-987-9779 www.Rollrock.com

Natural Stone is a relatively hard, naturally formed mineral or petrified matter, produced by nature. Therefore, considerable variations including, but not limited to, color, texture, size, and cleft will occur in all natural stone. Samples, sample panels, brochures, photographs, computer-generated pictures, and the Internet may be, in some measure, different from the stone you actually receive. Laboratory tests, if conducted, are performed on small samples and cannot be totally accurate because of the limited scale of the tests. Please be sure that all involved parties are aware of these facts, so an informed decision can be made regarding natural stone.

Use of Chemicals: Acid or chemical cleaners are not recommended because of the inability of the user to control its use, and are never recommended for Limestone and Marble. User accepts all risks.

DISCLAIMER OF WARRANTY AND DAMAGES:

Rolling Rock Building Stone Inc. products are provided to you "AS IS" without warranty of any kind, either expressed or implied, including, but not limited to the implied warranties of merchantability, or fitness for a particular purpose.

## Cappuccino™ Product Guide

## Pattern Cut Pavers

Nominal Size	Actual Size	Thickness	Average Pieces	Approx. Weight
Imperial, (inch)	Metric, (cm)	Inches, (cm)	Per Pallet	Per Pallet
				(lbs.)
4" x 8"	45 x 45	1 1/4"	816	3270
Mixed Sizes	French pattern		10	
14" x 24"		2"	50	3270



## Cappuccino™ Product Specifications

Geology: Marble

ASTM C97 Density: 167.6 lbs/ft<sup>3</sup> ASTM C97 Absorption: 0.41%


ASTM C99 Modulus of Rupture: 2070 PSI (Dry/ Perpendicular), 2330 PSI (Wet,

Perpendicular)

ASTM C170 Compressive Strength: 13,650 PSI (Dry/ Parallel), 17,090 PSI (Wet, Parallel) 17,250 PSI (Dry/ Perpendicular), 16,570 PSI (Wet, Perpendicular)

## Product Type & Finish:

- Pattern Cut Pavers: Sawn 6 sides, acid patina + tumbled finish.
- Sill, Tread, Cap, Heavy Step: Sawn 6 sides with 1 long bull nose (BN) edge; acid patina + tumbled finish.



Special Notice on Pattern Size: This product is an excellent choice for dry-laid work due to the stone's uniform thickness & cut-to-square quality in addition to the ability to match pieces without extensive field cutting.

(Example - Two 30 cm lengths = 60 cm.)

*Custom*: On larger jobs with proper planning and advance notice we can order special sizes or custom fabricated material from the factory to meet job specific requirements in an effort to reduce on site time and labor and reduce overall project cost. Please consult a sales representative for more information.







www.imPORTstone.net