



Rolling Rock Building Stone, Inc., 40 Rolling Rock Road, Boyertown, PA 19512
 Phone: (610) 987-6226, Fax: (610) 987-9779, Web: www.rollrock.com

Natural Stone is a relatively hard, naturally formed mineral or petrified matter, produced by nature. Therefore, considerable variations including, but not limited to, color, texture, size, and cleft will occur in all natural stone. Samples, sample panels, brochures, photographs, computer-generated pictures, and the Internet may be, in some measure, different from the stone you actually receive. Laboratory tests, if conducted, are performed on small samples and cannot be totally accurate because of the limited scale of the tests. Please be sure that all involved parties are aware of these facts, so an informed decision can be made regarding natural stone.

Use of Chemicals: Acid or chemical cleaners are not recommended because of the inability of the user to control its use, and are never recommended for Limestone and Marble. User accepts all risks.

DISCLAIMER OF WARRANTY AND DAMAGES:

Rolling Rock Building Stone Inc. products are provided to you "AS IS" without warranty of any kind, either expressed or implied, including, but not limited to the implied warranties of merchantability, or fitness for a particular purpose.

Islip™ Product Guide

Pattern Cut Pavers

Nominal Size Imperial, inch	Actual Size Metric, cm	Thickness Inches, (cm)	Average Pieces Per Crate	Approx. Weight Per Crate lbs.
24 x 24	60 x 60	1, (2.5cm)	36	2160
24 x 36	60 x 90			3240
Mixed Sizes	8 pc. pattern		82 = 200SF	3000

Coping

	Actual Size (Imperial) Inch x feet-inch	Thickness (Inches)	Average Pieces Per Pallet	Approx. Weight Per Pallet (lbs.)
Bull Nose	14 x 24	2	40	2800



Islip™ Product Specifications

Geology: Quartzite

Density ASTM C97: 176.5 lbs./ft³

Water Absorption ASTM C97: 0.13%

Compressive Strength ASTM C170:

Dry Parallel 26900 psi, Wet Parallel 15410 psi,

Dry Perpendicular 19990 psi, Wet Perpendicular 17580 psi

Modulus of Rupture ASTM C99: 2740 psi dry, 2850 psi, wet

Product Type & Finish:

Pattern Cut Pavers: Natural cleft top with sawn bottom & edges.

Coping: Natural Cleft with 1 long edge bullnose.

Pattern Cut Size: Islip™ Pavers are cut to near precise metric dimensions, producing a very high quality product having square corners. Imperial length and width measurements as indicated in inches reflect a nominal size which is approximately 1/2" short of the full dimension.

Special Notice on Pattern Size: This product is an *excellent* choice for dry-laid work due to the stone's uniform thickness & cut-to-square quality in addition to the ability to match pieces without extensive field cutting.

(Example - Two 30 cm lengths = 60 cm.)

Custom: On larger projects with proper planning and advance notice we can order special sizes or custom fabricated material from the factory to meet job specific requirements in an effort to reduce on site time and labor and reduce overall project cost. Please consult a sales representative for more information.



www.imPORTstone.net